

# VEP SERIES

## VESDA-E AIR SAMPLING DETECTOR



ActivFire VdS

EN 54-20, ISO 7240-20

### Four Pipe VEP

- Class A (40 holes / Fire 1 = 0.028% obs/m)
- Class B (80 holes / Fire 1 = 0.027% obs/m)
- Class C (100 holes / Fire 1 = 0.056% obs/m)

Classification of any configuration is determined using ASPIRE.

**P/N:** See Chart

The VESDA-E VEP series of smoke detectors bring the latest and most advanced detection technology to provide very early warning and the best nuisance alarm rejection to a wide range of applications. Built on the Flair detection technology and years of application experience, VEP detectors achieve consistent performance over their lifetime via absolute calibration. In addition, the VEP delivers a range of revolutionary features that provide user value.

### Flair Detection Technology

Flair is the revolutionary detection chamber that forms the core of the VESDA-E VEP, providing higher stability and increased longevity. Direct imaging of the sampled particles using a CMOS imager combined with multiple photo-diodes allows better detection and fewer nuisance alarms.

### Installation, Commissioning and Operation

VESDA-E VEP is equipped with a powerful aspirator that enables use of a total of 130m (427ft) of sampling pipe in the one pipe model and 560m (1,837ft) of pipe in the four pipe model. Out of box operation is made possible with AutoConfig which allows airflow normalisation and AutoLearn Smoke and Flow to be initiated from within the detector. VEP is fully supported by the ASPIRE and Xtralis VSC software applications which facilitate ease of pipe network design, system commissioning and maintenance.

### Features

- One and four pipe models for different applications
- Flair detection technology delivers reliable very early warning in a wide range of environments with minimal nuisance alarms
- Multi stage filtration and optical protection with clean air barriers ensures lifetime detection performance
- Four alarm levels and a wide sensitivity range deliver optimum protection for the widest range of applications
- Intuitive LCD icon display provides instant status information for immediate response
- Flow fault thresholds per port accommodate varying airflow conditions
- Smart on-board filter retains dust count and remaining filter life for predictable maintenance
- Extensive event log (20,000 events) for event analysis and system diagnostics
- AutoLearn™ smoke and flow for reliable and rapid commissioning
- Referencing to accommodate external environmental conditions to minimise nuisance alarms
- Backward compatible with VLP and VESDAnet
- Remote monitoring with iVESDA for system review and proactive maintenance
- Ethernet for connectivity with Xtralis software for configuration, secondary monitoring and maintenance
- USB for PC configuration, and firmware upgrade using a memory stick
- Two programmable GPIs (1 monitored) for flexible remote control
- Field replaceable sub-assemblies enable faster service and maximum uptime



## VESDAnet™

VESDA devices communicate on VESDAnet which provides a robust bidirectional communication network allowing continued redundant operation even during single point wiring failures. VESDAnet enables primary reporting, centralized configuration, control, maintenance and monitoring.


### Ethernet connectivity

VESDA-E detectors offer Ethernet connectivity as a standard feature.

### Backward Compatibility

VESDA-E VEP is compatible with existing VESDA installations. The detector occupies the same mounting footprint, pipe, conduit and electrical connector positioning as VESDA VLP. VEP is also compatible with existing VESDAnet installations allowing monitoring of both VESDA-E and legacy detectors via the latest iVESDA application.

## 3.5" Display



Symbol	LED
	Fire 2
	Fire 1
	Action
	Alert
	Disabled
	Fault
	Power

Home page	
Icon on display	Description
	Smoke and Alarm Threshold Levels
	Detector OK
	Detector Fault
	Aspirator Fault
	Airflow Fault
	Power Fault
	Filter Fault
	Smoke Chamber Fault
	VESDAnet Fault
	Stax Module Fault

Specifications					
	One Pipe VEP	Four Pipe VEP			
Supply voltage	18-30 VDC (24 V Nominal)				
Power consumption @ 24 VDC	VEP-A00-1P	VEP-A00-P		VEP-A10-P	
Aspirator Setting	Fixed	1	5	1	5
Power (Quiescent)	8.8 W	7.0 W	8.8 W	8.2 W	10.0 W
Power (In Alarm)	9.6 W	7.8 W	9.6 W	10.4 W	11.6 W
Dimensions (WHD)	350 mm x 225 mm x 135 mm (13.8 in x 8.9 in x 5.3 in)				
Weight	4.0 kg (8.8 lb)	4.0 kg (8.8 lb)		4.1 kg (9.0 lb)	
Operating conditions	Ambient: 0°C to 39°C (32°F to 102°F) Sampled Air: -20°C to 60°C (-4°F to 140°F) Tested to: -20°C to 55°C (-4°F to 131°F) UL: -20°C to 50°C (-4°F to 122°F) Humidity: 5% to 95% RH, non-condensing				
Area Coverage	1,000 m <sup>2</sup> (10,760 sq. ft)		2,000 m <sup>2</sup> (21,520 sq. ft)		
Min. airflow per pipe	15 l/m				
Pipe Length (Linear)	100 m (328 ft)		280 m (919 ft)		
Pipe Length (Branched)	130 m (427 ft)		560 m (1,837 ft)		
Pipe lengths depending on number of pipes in use	1 Pipe 100 m (328 ft)	1 Pipe 110 m (361 ft)	2 Pipe 100 m (328 ft)	3 Pipe 80 m (262 ft)	4 Pipe 70 m (230 ft)
StaX	PSU		PSU, Auto Pipe Clean		
No. of holes (A/B/C)	30/40/45		40/80/100		
Computer design tool	ASPIRE				
Pipe	Inlet: External diameter 25 mm or 1.05 in (3/4 in IPS) Exhaust: External diameter 25 mm or 1.05 in (3/4 in IPS) via adaptor				
Relays	7 programmable relays (latching or non-latching states) Contacts rated 2 A @ 30 VDC (Resistive)				
IP rating	IP40				
Cable access	4 x 26 mm (1.02 in) cable entries				
Cable termination	Screw Terminal blocks 0.2–2.5 sq mm (24–14 AWG)				
Dynamic Range	0.001% to 32% obs/m (0.0003% to 10% obs/ft)				
Sensitivity Range	0.005 to 20% obs/m (0.0016% to 6.25% obs/ft)				
Threshold setting range	Alert: 0.005% to 2.0% obs/m (0.0016% to 0.625% obs/ft) Action: 0.005% to 2.0% obs/m (0.0016% to 0.625% obs/ft) Fire1: 0.010% to 2.0% obs/m (0.0031% to 0.625% obs/ft) Fire2: 0.020% to 20.0% obs/m (0.0063% to 6.25% obs/ft)				
Software features	Event log: Up to 20,000 events Smoke level, user actions, alarms and faults with time and date stamp AutoLearn: Detector learns Alarm Thresholds and Flow Fault thresholds by monitoring the environment.				



**Ordering Information**

Model	P/N	Description
VEP-A00-1P	97119	VESDA-E VEP with LEDs, 1 pipe, Plastic Enclosure
VEP-A00-P	97593	VESDA-E VEP with LEDs, 4 pipe, Plastic Enclosure
VEP-A10-P	97592	VESDA-E VEP with 3.5" Display, 4 pipe, Plastic Enclosure

Accessories / Spare Parts		
VSP-960	97048	VESDA-E Mounting Bracket
VSP-961	97047	VESDA-E Exhaust adaptor US
VSP-962	97046	VESDA-E Filter
VSP-963	97045	VESDA-E Aspirator
VSP-964	97044	VESDA-E Smoke Detection Chamber
VSP-964-03	97043	VESDA-E Smoke Detection Chamber – MK3
VSP-965	97042	VESDA-E Sampling Module
VSP-968	97041	VESDA-E VEP-A00-P/1P Front Cover Plastic (LEDs)
VSP-969	97040	VESDA-E VEP-A10-P Front Cover Plastic (3.5" Display)

*Note: Approvals/Listings maintained by and manufactured by Xtralis AG.*

The seller makes no warranties, express or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose, except as expressly stated in the seller's sales contract or sales acknowledgment form. Every attempt is made to keep our product information up-to-date and accurate. All specific applications cannot be covered, nor can all requirements be anticipated. All specifications are subject to change without notice.



1102 Rupcich Drive  
 Crown Point, IN 46307  
 TEL: (219) 663-1600 FAX: (219) 663-4562  
 e-mail: [info@janusfiresystems.com](mailto:info@janusfiresystems.com)  
[www.janusfiresystems.com](http://www.janusfiresystems.com)